



NANOROD

Micro Profile LED Illuminated Closet Rod

Customer:

Date:

Type:

Project:



- Compact, variable light fixture for dry location use only.
- Fixture comes in 4" increments (12" minimum).
- Many options in color temperature to suit a range of projects.
- Fixtures offer 50lb/ft load capability with proper mounting.
- Can use standard line voltage dimming.
- Standard design for ease of integration in existing spaces.
- Closet rated-Interior installation use only.
- Contact Boca Flasher for tips with custom installations.




PRODUCT SPECIFICATIONS:

	WATTAGE	COLOR OPTION	OPTIC	VOLTAGE	FINISH	LENS	MOUNTING
NanoRod	CL		120°	120V	A		
	4W	2400K			A Clear Anodized Aluminum	C Clear	EC End Mount - Mounts Up to 36"
	8W	2700K			*Contact Agent for Other Options	D Diffused	EC1 End Mount With 1 Support - Mounts 36-72"
		3000K				OW Opal White	EC2 End Mount With 2 Supports - Mounts 72"-96"
		3500K					
		4000K					
		5000K					

DIMENSIONS:

Plan View



Elevation View



NANOROD

Micro Profile LED Illuminated Closet Rod



TECHNICAL SPECIFICATIONS:

WATTAGE	4 or 8 watts per linear ft.
INPUT VOLTAGE	120VAC
CONTROL	Leading Edge/Trailing Edge line dimmer, 0-10V*
LED SPACING	5/8" on center
LENGTH	12"-96" in 4" Increments, Allow 1" For Each End Cap
TOTAL WIDTH	1.20"
TOTAL HEIGHT	1.20"
COLOR OPTIONS	2400K, 2700K, 3000K, 3500K, 4000K, 5000K
MOUNTING	End, Center
AVAILABLE OPTICS	120°
COLOR RENDERING INDEX (CRI)	90 + CRI
RATING	IP50 Interior Only
POWER CABLE	UL Standard 10 ft.
ENVIRONMENTAL	Operating temperature--40°F-140°F Ambient(-40°C-60°C)** Storage temperature -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

*Requires Boca SDS Dimming Interface

** Military spec available under special request-lead times may be impacted.

MOUNTING INFORMATION:

