


MOUNTING OPTIONS



MOUNTING TAPE TUBE
(using approved adhesive tape fixture can rotate in tube)

TECHNICAL DATA	
Parameter	Data
Power	4.8W/ft for (20°, 50°), 6W/ft for 120°
Input Voltage	24VDC or 24VAC
Input Current per Linear Ft	180mA RMS per Linear Foot
Control	Standard Magnetic Low Voltage Dimming
Power Cable Length	25ft, 35ft, or 45ft (Job Specific)
LED Spacing	0.5" on center
Fixture Length	4" increments (white, b, g), 6" increments(r,a)
Fixture Width	0.62"
Total Height (not including clips)	0.41"
Mounting	Tube, Underwater Tube, No Tube
Available Optics	20°, 50°, 120°, or 30° (amber, r, g, b only)
Finish Options	N/A
LED Color Options	3K, 5K, amber, red, green, blue
Color Rendering Index	80
Ratings	Dry, IP66, IP68
Total Linear ft per 20A breaker	90 Feet
Total Linear ft per 15A breaker	65 Feet
Total Linear ft per Power Feed	20 Feet
Transformer	Primary 120V or 277V, Secondary 24V

<p>508 South Military Trail Deerfield Beach FL, 33442</p> <p>www.BocaFlasher.com (561) 989-5338</p>		PRODUCT NAME: <h2>AC100 DOUBLE</h2>	
		FILE NAME: TECHNICAL SHEET	PART #: AC100-1
DRAWN BY: DEMMLER FILLINGER		DATE: 03272020	
DESIGN BY: LUIS ROSADO			
APPROVED BY: ANGELA TODD			
THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHTS OF BOCA FLASHER INC.		SCALE: NTS	SHEET: 1 OF 1
		REV: A	