
HPNLS-MIX

Small Profile Color Changing LED Fixture

Customer: Date: Type:

Project:





Wattage	14W per linear ft*
Input Voltage	90-120V, 230-277V
Control	Standard DMX 512
LED Spacing	1.0" on Center
Length	12"-96", in 12" increments
Total Height	1.68"
Total Width	1.80" (not including clip)
Color Options	Alternating RGB, RGBW, Triple Diode RGB, White Mixing
Mounting	Fixed, Hinge, Vandal, Arc 3 or Arc 6
Available Optics	10°x10°, 30°x30°, 60°x 60°, 10°x30°, 10°x60°, 30°x60°, 80°x80°, 100°x100°
Rating	IP50, IP67, IP69K
CRI	90+ for White Mix Only
Power Cable	UL Standard 10 ft
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

*Custom wattage available upon request. Title 24 compliant fixture not to exceed 18 watts / 4ft fixture.
** Military spec available under special request-lead times may be impacted.

KEY FEATURES:

- Color configurations include RGB, RGBW, triple-diode RGB and white mixing.
- 14W per linear foot with DMX 512 control.
- Multiple optic distributions, including 80° × 80° and 100° × 100°.

PRODUCT SPECIFICATIONS:

PRODUCT	COLOR OPTION	VOLTAGE	OPTIC	FINISH	LOCATION	MOUNTING	LENS	WHITE MIXING OPTIONS*	OPTIONS
HPNLS-MIX									
	RGB **RGBW** **TRGB** Triple Diode (120° only) **WM** White Color Mixing *See White Mix Options	**120V** **277V**	**10°x10°** **30°x30°** **60°x60°** **10°x30°** **10°x60°** **30°x60°** **80°x80°** **100°x100°**	**W** White **B** Black **G** Gray	**I** Interior-IP50 **E** Exterior-IP67 **N** Natatorium* **K** IP69K-Extreme Enviroment *Chromate Conversion with Marine Grade Powder Coat-IP67. Extra Charges may apply.	**F** Fixed **S** Swivel **H** Hinge **3Arc** 3" Arc Swivel **6Arc** 6" Arc Swivel **V** Vandal Proof Clip	**C** Clear **D** Diffused **SI** Satin Ice (Interior Use Only) **OP** Opal White	**2700K** **3000K** **3500K** **4000K** **5000K** **Amber** *If specifying WM indicate white options here: (Up to 3 different options can be specified)	**SB** Square Baffle **ASYM** Asymmetric Baffle **SKB** Kicker Baffle **HL** Hexcell Louver* *Cannot be used with Satin Ice White or 120° optic

Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323

We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls

REV11112026