

Customer:	Date:	Туре:	
Project:			



Wattage	4W or 8W per linear ft.			
Input Voltage	120VAC			
Control	Forward/Reverse Phase Line Dimmer, 0-10V*			
LED Spacing	5/8" on Center			
Length	12"-96" in 4" increments. Allow 1" for each end cap.			
Total Width	1.20"			
Total Height	1.20"			
Color Options	2400K, 2700K, 3000K, 3500K, 4000K, 5000K			
Mounting	Fixed, End			
Available Optics	120°x120°			
CRI	90+ CRI			
Rating	IP50, Closet Rated - Interior Only			
Power Cable	UL Standard 10 ft.			
Material	Anodized Aluminum			
Finish	Clear Anodized Aluminum			
Custom	Contact Factory			
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity			













PRODUCT SPECIFICATIONS:

PRODUCT	WATTAGE	COLOR OPTION	VOLTAGE	OPTIC	FINISH	MOUNTING	LENS
NANOROD							
	4W 8W	2400K 2700K 3000K 3500K 4000K 5000K	120V	120°x120°	A Clear Anodized Aluminum	EC End Mount - Mounts Up to 36" EC1 End Mount With 1 Support - Mounts 36-72" EC2 End Mount With 2 Supports - Mounts 72"-96"	C Clear D Diffused OW Opal White
					*Contact factory for custom options		

^{*}Requires Boca SDS Dimming Interface


^{**} Military spec available under special request-lead times may be impacted.







DIMENSIONS:



MOUNTING INFORMATION:

