HPNFC-HO

Interior Shallow Profile Linear
LED Strip Fixture

Customer: Date: Type:

Project:





*Contact Factory for Exterior Installations

Wattage	5, 8 or 10W per linear ft.
Input Voltage	90-120V or 230-277V
Control	Forward/Reverse Phase Line Dimmer, 0-10V, DALI, DMX*
LED Spacing	1.5” on center
Length	12”-96”, 6” increments - 12” minimum
Total Height	1.04” (not including clip), Satin Ice Lens adds 1/8”
Total Width	1.68”
Color Options	2700K, 3000K, 3500K, 4000K, 5000K, Amber, Red, Green, Blue
Mounting	Fixed, Swivel, 3” Arc or 6” Arc
Available Optics	10°x10°, 30°x30°, 60°x 60°, 10°x60°, 30°x60°, 120°x120°
Max Run	8W=80 ft., 10W=65 ft. Per Power Feed
Rating	IP50 - Contact Factory for IP67, IP69K
CRI	90+ CRI
Power Cable	UL Standard 10 ft.
Finish	White, Black and Gray
Materials	Anodized Aluminum
Custom	Contact Factory
Dimming	Patented CleanDim® Technology ensures even dimming from 0-100%.
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

*Uses Boca SDS Module for 0-10V, DALI, or DMX Dimming.
** Military spec available under special request-lead times may be impacted.

KEY FEATURES:

- Shallow 1.04” profile with 5W, 8W or 10W per linear foot.
- Patented CleanDim® Technology delivers even dimming from 0–100%.
- Supports phase, 0–10V, DALI and DMX dimming.

PRODUCT SPECIFICATIONS:

PRODUCT	LED SPACING	COLOR OPTION	VOLTAGE	OPTIC	FINISH	LOCATION	MOUNTING	LENS	OPTIONS
HPNFC-HO									
	HO8 5W/FT **HO8** 8W/FT **HO8** 10W/FT	**2700K** **3000K** **3500K** **4000K** **5000K** **Amber** **Red** **Green** **Blue**	**120V** **277V**	**10°x10°** **30°x30°** **60°x60°** **10°x60°** **30°x60°** **120°x 120°**	**W** White **B** Black **G** Gray	**I** Interior-IP50 *Contact factory for IP67, IP69K	**F** Fixed **S** Swivel **H** Hinge **3Arc** 3” Arc Swivel **6Arc** 6” Arc Swivel	**C** Clear **D** Diffused **SI** Satin Ice (Interior Use Only)	**SB** Square Baffle **ASYM** Asymmetric Baffle **SKB** Kicker Baffle **HL** Hexcell Louver* *Cannot be used with Satin Ice White or 120° optic

Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323

We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls

REV11112026