


TRI-LIGHT HV



























^{*} Contact factory for Extreme Environment Installations.

| Customer: | Date: | Туре: | |
|-----------|-------|-------|--|
| Project: | | | |

| Wattage | 12W Max, Software Controlled | | | |
|------------------|--|--|--|--|
| Input Voltage | 120VAC | | | |
| Control | Nanorouter w/ standard DMX512 control | | | |
| LED Spacing | 1.00" | | | |
| Length | 12"-96", 6" increments | | | |
| Total Width | 1.68" | | | |
| Total Height | 1.75" | | | |
| Mounting | Fixed, Swivel, Hinge, Arc or Vandal Resistant | | | |
| Available Optics | 120°x120° | | | |
| Finish | Black, White or Gray Powder Coat | | | |
| Color Options | Triple Diode RGB, or Triple Diode RGB w/ White Option | | | |
| Input Current | 120VAC | | | |
| Rating | IP50, IP67 | | | |
| Power Cable | 25 ft Home Run Cable | | | |
| CRI | Specifiable | | | |
| Material | Anodized Aluminum | | | |
| Max Run | 48ft. per Power Feed | | | |
| Environmental | Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity | | | |
| | | | | |

^{**} Military spec available under special request-lead times may be impacted.


PRODUCT SPECIFICATIONS:

| PRODUCT | COLOR OPTION | VOLTAGE | OPTIC | FINISH | MOUNTING | LOCATION | LENS |
|--------------|--|---------|-----------|------------------------------|---|------------------------------------|--|
| TRI-LIGHT HV | | | | | | | |
| | 1 Triple Diode RGB 2 RGB with White | 120VAC | 120°x120° | W White B Black G Gray | F Fixed S Swivel H Hinge V Vandal Resistant A Arc | I Interior-IP50 E Exterior-IP67 | C Clear D Diffused SI* Satin Ice (Interior Use Only) OW** Opal White |
| | | | | | | | *Interior Use Only **Exterior Use Only |




DIMENSIONS:

For vertical installation and installations above 4' please contact the factory for specific mounting instructions.




Plan View




Elevation View

MOUNTING INFORMATION:


Note: Fixtures 1-2ft, Place clips 3" from edge as shown. Fixtures more than 2ft., Place clips 3.5" from edges as shown.



Swivel



Hinge



LENS OPTIONS:

DIFFUSED GLASS

- 87% transmission
- Lens is 1/8" (.09) thick, adds
 1/16" to overall height of fixture
- Additional charges apply

SATIN ICE WHITE

- Best for direct view use. Interior use only.
- 42% transmission
- Lens is 1/4" (.25) thick, adds 1/8" to overall height of fixture
- Additional charges apply