

TRI-LIGHT RT

Triple Diode DMX Controlled Linear LED Fixture

Customer:	

Project:

Date:

Wattage	8W per linear ft for RGB, 10W per linear ft for RGBW						
Input Voltage	24 VAC						
Control	IMCS box w/ standard DMX512 control						
LED Spacing	0.44" on Center						
Length	12"-96", 6" increments						
Total Width	1.68"						
Total Height	1.75" (not including clip)						
Mounting	Fixed, Swivel, Arc or Vandal Resistant						
Available Optics	120° Black, White or Gray powder coat						
FInish							
Color Options	Triple diode RGB, or triple diode RGB w/ white option						
CRI	Specifiable						
Rating	IP50, IP65, IP68						
Power Cable	30 ft home run cable						
Material	Anodized Aluminum						
Max Run	8ft. (Class 2 Limited)						
Environmental	Operating temperature40°F-140°F Ambient(-40°C-60°C)** Storage temperature -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity						

** Military spec available under special request-lead times may be impacted.

* Contact factory for Extreme Environment Installations.

IP69K

ВАВА

PRODUCT SPECIFICATIONS:

IP67

US

IP50

		COLOR OPTION	OPTIC	PRIMARY VOLTAGE	FI	INISH	LOCATION	MOUNTING	LENS	OPTION
	Iri-Light RI	Tri-Light RT	1 20 °							
		1 Triple Diode RGB 2 RGB with White		120V 277V (Light is 24VAC)	W White B Black G Gray		l Interior-IP50 E Exterior-IP67	F Fixed S Swivel H Hinge V Vandal Resistant A Arc	C Clear D Diffused SI Satin Ice (Interior Use Only) OW Opal White	

Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323


We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls

(Exterior Use Only)




DIMENSIONS:

For vertical installation and installations above 4' please contact the factory for specific mounting instructions.



MOUNTING INFORMATION:

Note: Fixtures 1-2ft, Place clips 3" from edge as shown. Fixtures more than 2ft., Place clips 3.5" from edges as shown.






LENS OPTIONS:

DIFFUSED GLASS


- 87% transmission
- Lens is 1/8" (.09) thick, adds 1/16" to overall height of fixture
- Additional charges apply

SATIN ICE WHITE

- Best for direct view use. Interior use only.
- 42% transmission -
- Lens is 1/4" (.25) thick, adds 1/8" _ to overall height of fixture
- Additional charges apply _







Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323

We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls