



TRI-LIGHT RT

Triple Diode DMX
Controlled Linear LED Fixture



* Contact factory for Extreme Environment Installations.

Customer: _____ Date: _____ Type: _____

Project: _____

Wattage	8W per linear ft for RGB, 10W per linear ft for RGBW
Input Voltage	24 VAC
Control	IMCS box w/ standard DMX512 control
LED Spacing	0.44" on Center
Length	12"-96", 6" increments
Total Width	1.68"
Total Height	1.75" (not including clip)
Mounting	Fixed, Swivel, Arc or Vandal Resistant
Available Optics	120°x120°
Finish	Black, White or Gray powder coat
Color Options	Triple diode RGB, or triple diode RGB w/ white option
CRI	Specifiable
Rating	IP50, IP65, IP68
Power Cable	30 ft home run cable
Material	Anodized Aluminum
Max Run	8ft. (Class 2 Limited)
Environmental	Operating temperature--40°F-140°F Ambient(-40°C-60°C)** Storage temperature -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity


** Military spec available under special request-lead times may be impacted.

PRODUCT SPECIFICATIONS:


PRODUCT	COLOR OPTION	VOLTAGE	OPTIC	FINISH	MOUNTING	LOCATION	LENS	OPTION
TRI-LIGHT RT	1 Triple Diode RGB 2 RGB with White	120V 277V (Light is 24VAC)	120°x120°	W White B Black G Gray	F Fixed S Swivel H Hinge V Vandal Resistant A Arc	I Interior-IP50 E Exterior-IP67	C Clear D Diffused SI* Satin Ice (Interior Use Only) OW** Opal White *Interior Use Only **Exterior Use Only	

DIMENSIONS:

For vertical installation and installations above 4' please contact the factory for specific mounting instructions.




Plan View




Elevation View

MOUNTING INFORMATION:


Note: Fixtures 1-2ft, Place clips 3" from edge as shown. Fixtures more than 2ft., Place clips 3.5" from edges as shown.



Swivel



Hinge



Fixed

Vandal Resistant

LENS OPTIONS:

DIFFUSED GLASS

- 87% transmission
- Lens is 1/8" (.09) thick, adds 1/16" to overall height of fixture
- Additional charges apply

SATIN ICE WHITE

- Best for direct view use. Interior use only.
- 42% transmission
- Lens is 1/4" (.25) thick, adds 1/8" to overall height of fixture
- Additional charges apply