




1 PLAN VIEW
SCALE: 6"=1'-0"



2 ELEVATION VIEW
SCALE: 6"=1'-0"





3 END CAP
SCALE: 6"=1'-0"



4 SECTION
SCALE: 6"=1'-0"


MOUNTING OPTIONS



TECHNICAL DATA

Parameter	Data
Wattage per Linear Ft.	7.0W @ 120V
Input Voltage	90-120VAC
Input Current per Linear Ft.	160.9mA @ 120V
Control	Leading edge/ Trailing-edge line dimmer
Power Cable Length	UL Standard 18AWG, 6.5ft.
LED Spacing	0.61"
Fixture Length	12"-72" in 4" increment
Fixture Width	1.11"
Total Height (Not Including Clip)	0.95"
Mounting	Adjustable Swivel Clip
Available Optics	120°
Finish Options	White or Black high temperature ABS Plastic
LED Color Options	2K, 24K, 27K, 3K, 35K, 4K, 5K, 65K
Color Rendering Index	90+ CRI
Ratings	Dry
Total linear ft per 20A breaker	99ft. @ 120V
Total linear ft per 15A breaker	74ft. @ 120V
Total linear ft per power feed	24ft. @ 120V
Transformer	N/A

END CAP CONDITIONS



LED Lighting Systems, Technologies, & Manufacturing

508 South Military Trail
Deerfield Beach FL, 33442

www.boca.lighting
(561)989-5338

THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY
COPYRIGHTS OF BOCA LIGHTING AND CONTROLS

PRODUCTS NAME:
NANOTUNE

FILE NAME: TECHNICAL SHEET

PART #: BF-NANOTUNE

DRAWN BY: HYORIM LEE

DATE: 04032025

DESIGN BY: LUIS ROSADO

APPROVED BY: DAVE URBAN

SCALE: NTS

SHEET: 1 OF 1

REV: 04032025