NANO PIXEL PRELIMINARY

Multi Diode DMX Controlled Line Voltage
Small Profile Linear LED Fixture

Customer: Date: Type:

Project:





Wattage	5W per linear ft.
Input Voltage	90-120VAC, 277VAC, 380VDC
Control	NanoPixel Router, Operates with standard 512 DMX, ArtNet, NanoFlux™
Power Cable	10 ft., 25 ft., 100 ft.
Length	12", 24", 48"
Input Current	Run Dependent
Mounting	Channel Fixed ,Channel Hinge
Availabe Optics	120°x120°
Finish	Marine Grade Anodized Aluminum
Color Options	RGBW, RGBA,RGBL Selectable White CCT
Max Run	Run/Wattage Dependent e.g. 2W-1600'@277VAC,5W-760'@277
Rating	IP66
CRI	90 + CRI-WHITE LED
Material	Marine Grade Anodized Aluminum, Marine Grade Powder Coat*
Custom	Contact Factory
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

**Additional Charges may apply
** Military spec available under special request-lead times may be impacted.

KEY FEATURES:

- Multi-diode linear fixture designed for dynamic, individually controlled lighting.
- RGBW, RGBA and RGBL configurations with selectable white CCT options.
- NanoPixel Router control supports DMX, Art-Net and NanoFlux™

PRODUCT SPECIFICATIONS:

PRODUCT	WATTAGE	COLOR OPTION	VOLTAGE	OPTIC	FINISH	MOUNTING	LENS
NANO PIXEL	**5W**			**120°x120°**			
	5W	**RGB(W):** ***PICK 4TH CHIP*** **2000K** **2400K** **2700K** **3000K** **3500K** **4000K** **5000K** **6500K** **Red** **Blue** **Amber** **Green Lime**	**120VAC** **277VAC** **380VDC**	**120°x120°**	**A** Clear Anodized Aluminum **N** Natatorium Finish* **C** Custom* *Additional charges may apply	**F** Fixed **H** Hinge **B** Blank	**CLD** Clear Light Diffused **C** Clear **O** Opal *Not Available with Optics

Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323

We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls