


TECHNICAL DATA	
Parameter	Data
Wattage	8W software controlled
Input Voltage	90-120V or 230-277V
Input Current per Linear Ft	54mA@1 20V or 24mA@277V
Control	Leading-edge/Trailing-edge line dimmer
Power Cable Length	UL Standard 10ft
LED Spacing	0.67" on center
Fixture Length	12", 24", 48"
Fixture Width	1.21" Fixed Clip
Total Height	1.21" Fixed Clip
Mounting	Fixed clip/Swivel/Hinge
Available Optics	15°x45°,120°
Finish Options	Anodized Aluminum
LED Color Options	2000K, 2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6500K
Color Rendering Index	90+ CRI
Ratings	IP65,IP67
Total linear ft per 20A breaker	210ft@1 20V or 470ft@277V
Total linear ft per 15A	156ft@1 20V or 350ft@277V
Total linear ft per power feed	76ft@1 20V or 1 56ft@277V
Transformer	N/A

 <p>LED Lighting Systems, Technologies, & Manufacturing</p>		PRODUCT NAME: <h1>NANOX</h1>	
508 South Military Trail Deerfield Beach FL, 33442		www.BocaFlasher.com (561) 989-5338	
THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHTS OF BOCA FLASHER INC.		FILE NAME: TECHNICAL SHEET	PART #: NANOX
		DRAWN BY: HYERI KANG	DATE: 03272020
DESIGN BY: LUIS ROSADO			
APPROVED BY: M. PINDER			
SCALE:	SHEET: 1 OF 1	REV: A	