



























*Contact Factory for Exterior Installations

\M/-44	4141 a. 2141 a. a. linaan fi						
Wattage	4W or 8W per linear ft.						
Input Voltage	90-120V or 230-277V						
Control	Forward/Reverse Phase Line Dimmer 0-10V, DALI, DMX*						
LED Spacing	0.66" on center						
Length	$12^{\prime\prime}\text{-}96^{\prime\prime}$, $6^{\prime\prime}$ increments. Allow $1/4^{\prime\prime}$ for each end cap, $2^{\prime\prime}$ for power feed cable.						
Total Height	1.24" (not including clip), Satin Ice Lens adds 1/8"						
Total Width	1.68"						
Color Options	2000K, 2400K, 2700K, 3000K, 3500K, 4000K, 5000K						
Mounting	Fixed, Swivel, 3" Arc or 6" Arc						
Available Optics	120°x120°						
Rating	IP50, IP67*, IP69K*						
CRI	90+ CRI						
Power Cable	UL Standard 10 ft.						
Finish	Black, White, Grey						
Material	Anodized Aluminum						
Custom	Contact Factory						
Dimming	Patented CleanDim® Technology ensures even dimming from 0-100%.						
Max Run	56ft @120V or 120ft @277V						
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)* Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity						


PRODUCT SPECIFICATIONS:

PRODUCT	WATTAGE	COLOR OPTION	VOLTAGE	OPTIC	FINISH	LOCATION	MOUNTING	LENS	OPTIONS
LUMELINE									
	4W 8W	2000K 2400K 2700K 3000K 3500K 4000K 5000K	120V 277V	120°x 120°	W White B Black G Gray	I Interior-IP50	F Fixed S Swivel H Hinge 3Arc 3" Arc Swivel 6Arc 6" Arc Swivel	C Clear D Diffused SI Satin Ice (Interior Use Only) OW Opal White (Exterior Use Only)	SB Square Baffle ASYM Asymmetric Baffle SKB Kicker Baffle
						*Contact factory for IP67 and IP69K.			

^{*}Uses Boca SDS Module for 0-10V, DALI, or DMX Dimming.
** Military spec available under special request-lead times may be impacted.




DIMENSIONS:




MOUNTING INFORMATION:

For vertical installation and installations above 4' please contact the factory for specific mounting instructions.




Fixed





Hinge



Arc

LENS OPTIONS:

DIFFUSED GLASS

- 87% transmission
- Lens is 1/8" (.09) thick, adds 1/16" to overall height of fixture
- Additional charges apply

SATIN ICE

- Best for direct view use. Interior use only.
- 42% transmission
- Lens is 1/4" (.25) thick, adds 1/8" to overall height of fixture
- Additional charges apply