


TECHNICAL DATA	
Parameter	Data
Wattage	8W software controlled
Input Voltage	90-120V/240-277V
Input Current per Linear Ft	88mA@120V/40mA@277V
Control	DMX/NanoRouter
Power Cable Length	UL Standard 10ft
LED Spacing	1.0" on center
Fixture Length	12"-72", in 6" increment
Fixture Width	1.21" Fixed Clip
Total Height	0.82" (not including clip)
Mounting	Fixed clip/Swivel/Hinge
Available Optics	15°x45°, 120°
Finish Options	Anodized Aluminum
LED Color Options	2000K, 2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6500K
Color Rendering Index	93+ CRI
Ratings	IP65, IP67
Total linear ft per 20A breaker	180ft@120V/400ft@277
Total linear ft per 15A	120ft@120V
Total linear ft per power feed	46ft@120V/100ft@277
Transformer	N/A



LED Lighting Systems, Technologies, & Manufacturing

PRODUCT NAME:
NANOMIX-EXT

FILE NAME: Technical		PART #: NANOMIX-EXT	
DRAWN BY: HYERI KANG		DATE: 03272020	
DESIGN BY: LUIS ROSADO			
APPROVED BY: M. PINDER			
508 South Military Trail Deerfield Beach FL, 33442		www.BocaFlasher.com (561) 989-5338	
THIS DOCUMENT IS CONFIDENTIAL AND PROTECTED BY COPYRIGHTS OF BOCA FLASHER INC.			
SCALE:	SHEET: 1 OF 1	REV: B	