HPFB

Medium Profile Color Changing LED Fixture

Customer: _____ Date: _____

Project: _____



*Contact factory for Extreme Enironment Installations

Wattage	32W per linear ft.*
Input Voltage	120 V or 277 V
Control	Standard DMX 512, WA5 required for wireless transmission
LED Spacing	1.0" on center
Length	1 ft., or 4 ft.
Total Height	2.51" (not including clip)
Total Width	4.19"
Color Options	RGB, RGBW, RGB/WWW, RGB/WWA
Mounting	Fixed, Swivel, or Vandal Resistant
Available Optics	10°x 10°, 30°x 30°, 60°x 60°, 10°x30°, 10°x60°, 30°x60°, 120°x120°
Rating	IP50, IP67, IP69K
CRI	90+ for White Mixing Only
Power Cable	UL Standard 10 ft.
Material	Anodize Aluminum Housing
Lens	Clear, Diffused (interior only)
Custom	Contact Factory
Environmental	Operating temperature: -40°F-140°F Ambient(-40°C-60°C)** Storage temperature: -40°F-140°F Ambient indoor fixtures operation limited to =<50% relative humidity

*Custom wattage available upon request. Title 24 compliant fixture not to exceed 18 watts / 4ft fixture.
** Military spec available under special request-lead times may be impacted.

KEY FEATURES:

- Color configurations include RGB, RGBW, RGB/WWW and RGB/WWA.
- DMX 512 control with 3-, 4-, 6- and 8-channel configurations.
- IP50, IP67 and IP69K ratings with fixed, swivel and vandal-resistant mounting.

PRODUCT SPECIFICATIONS:

PRODUCT	COLOR OPTION	VOLTAGE	OPTIC	FINISH	LOCATION	MOUNTING	LENS	WHITE MIXING OPTIONS	CONTROLS	HEXCELL
HPFB							C	Amber Amber Amber		
	RGB **RGBW** color & white* **RGB/WWW** **RGB/WWA** *See White Mix Options	**120V** **277V**	**10°x10°** **30°x30°** **60°x60°** **10°x30°** **10°x60°** **30°x60°** **120°x120°**	**A** Clear Anodized Aluminum	**I** Interior-IP50 **E** Exteri-or-IP67	**F** Fixed **H** Hinge **V** Vandal Resistant	**C** Clear	**2200K** **2400K** **2700K** **3000K** **3500K** **4000K** **5000K** **Amber** If specifying WM indicate white options here: (Up to 3 different options can be specified)	**3** 3 Channel DMX **4** 4 Channel DMX **6** 6 Channel DMX **8** 8 Channel DMX	**Y** Yes **N** No

Boca Lighting and Controls · www.Boca.Lighting · Phone: 561-989-5338 · Fax: 561-982-8323

We are constantly improving our fixtures and reserve the right to change options and specifications. For specific requirements, contact your Boca Lighting and Controls sales representative. This product complies with IES LM-79-08 testing procedures and relevant standards. All products proudly manufactured in the USA. All rights reserved. All names and trademarks are property of their respective owners. © 2024 Boca Lighting and Controls