

ustomer:	Date:	 Туре:	
Project:			



Wattage	6W per linear ft.
Input Voltage	12-48VAC
Control	Standard Magnetic Low Voltage Dimming
LED Spacing	1.5" on center
Tube Length	15" - 123" in 6" increments, 10' maximum length
Total Height	2.01" (including clip)
Total Width	2.10" (including clip)
Total Diameter	1.75"
Color Options	2700K,3000K, 3500K, 4000K, 5000K, Amber, Red, Green, Blue
Available Optics	10°x10°, 30°x30°, 60°x60°, 10°x60°, 30°x60°, 120°x 120°
Rating	IP50, IP67
CRI	90+ CRI
Power Cable	Variable
Materials	Tempered polycarbonate housing tube, all metal parts are Teflon coated
Environmental	Operating temperature: $-40^{\circ}F-140^{\circ}F$ Ambient($-40^{\circ}C-60^{\circ}C$)** Storage temperature: $-40^{\circ}F-140^{\circ}F$ Ambient indoor fixtures operation limited to =<50% relative humidity

^{**} Military spec available under special request-lead times may be impacted.











PRODUCT SPECIFICATIONS:


PRODUCT	COLOR OPTION	TRANSFORMER VOLTAGE	OPTIC	HOUSING	OPTION
HPSUB RT					
	2700K 3000K 3500K 4000K 5000K Amber Red Green Blue	120V 277V	10°x 10° 30°x30° 60°x60° 10°x60° 30°x60° 120°x120°	UW Underwater Tube	
		If ordering 17VDC fixture, make note here and contact factory - (Fixture is 12-48VAC)			







Solid Color Submersible LED Light Strips

DIMENSIONS:







End Cap

Section In Tube

MOUNTING INFORMATION:

Fixed

